



	Standard	Result
Thickness		2.0 mm
Size		See separate table
Wear layer		12 mil (0.30 mm)
Surface treatment		Anti-scratch UV coating
Warranty ¹	Commercial Residential	10 Years Lifetime
Beveled Edge		No
Classification	ASTM F1700	Class III Type B
Reaction to fire	ASTM E648-06	Class 1
Smoke density	ASTM E662-06	Pass (< 450)
Flammability test	FF 1-70; Federal Approval	Pass
Slip resistance ²	ASTM D2047	Pass (Dry 0.91)
Staining resistance	ASTM F925	Pass
Light fastness	ASTM F1515	Pass $\Delta E = 1.3$
Abrasion resistance	ASTM D3884	Pass (16,000 Cycles)
Dimensional stability	ASTM F2199	Pass 0.004"/lin.ft
Acoustic impact noise reduction	ASTM E2179-09 ASTM E492-09	$\Delta IIC = 4$ dB IIC = 43 dB (6" Concrete Slab w/Drop Ceiling) IIC = 70 dB (6" Concrete Slab w/Drop Ceiling + QuietChoice)
Static load	ASTM F970	1,500 psi
Flexibility	ASTM F137	Pass
Adhesive		DrySet K-Spray Karndean Epoxy K99 HM
Environmental	FloorScore® SCS-EC10.3-2014 v4.0 Environmental Product Declaration NSF / ANSI 332 ISO 14001 / ISO 9001	Indoor air quality certified; Compliant low emitting VOC emissions. External third-party verified Type III EPD Sustainability Assessment for Resilient Floor Coverings; Conformant product Manufactured to quality and environment management systems standards
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms. Commercial warranty covers light commercial use only

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

Feb 23

For more information:

Email: info@kbsfloors.com

Visit: www.kbsfloors.com
